(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1Date of compilation: 18/06/2019Version 11 (replaces version 10)Revision date: 23/12/2021

Page 1 of 11 Print date: 23/12/2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:

MAXIGEAR SYN 220

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Transmission oil

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	OLIPES SL
Address:	C/ ALUMINIO, 2-3 (Parque Empresarial Borondo)
City:	Campo Real - 28510
Province:	Madrid (Spain)
Telephone:	+0034918765244
Fax:	+0034918733886
E-mail:	calidad@olipes.com
Web:	www.olipes.com

1.4 Emergency telephone number: (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008: Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:				
H statements:				
H412	Harmful to aquatic life with long lasting effects.			
P statements: P273 P501	Avoid release to the environment. Dispose of contents/container in accordance with the legislation in force.			

EUH statements: EUH208

Contains Polysulfides, di-tert-Bu. May produce an allergic reaction.

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable. Distillates (petroleum), solvent-dewaxed heavy parafinic **3.2 Mixtures.**

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1Date of compilation: 18/06/2019Version 11 (replaces version 10)Revision of

Revision date: 23/12/2021

Page 2 of 11 Print date: 23/12/2021

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008		
Identifiers	Name	Concentrate	Classification	specific concentration limit	
Index No: 649-483- 00-5 CAS No: 72623-87-1 EC No: 276-738-4 Registration No: 01- 2119474889-13-XXXX	[1] lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil — unspecified, [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 oC. It contains a relatively large proportion of saturated hydrocarbons.]	25 - 49.99 %	-	-	
Index No: 649-468- 00-3 CAS No: 64742-55-8 EC No: 265-158-7 Registration No: 01- 2119487077-29-XXXX	[1] distillates (petroleum), hydrotreated light paraffinic, Baseoil — unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	0 - 9.99 %	Asp. Tox. 1, H304	-	
CAS No: 68457-79-4 EC No: 270-608-0 Registration No: 01- 2119493628-22-XXXX	Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	1 - 2.49 %	Aquatic Chronic 2, H411 - Eye Dam. 1, H318 - Skin Irrit. 2, H315	Eye Dam. 1, H318: C ≥ 3 % Skin Irrit. 2, H315: C ≥ 15 %	
CAS No: 1330-78-5 EC No: 215-548-8 Registration No: 01- 2119531335-46-XXXX	tris(methylphenyl) phosphate	0.25 - 2.49 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Repr. 2, H361fd	-	
Index No: 649-474- 00-6 CAS No: 64742-65-0 EC No: 265-169-7 Registration No: 01- 2119471299-27-XXXX	[1] distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil — unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 oF (19cSt at 40 oC).]	0 - 2.49 %	-	-	
CAS No: 68937-96-2 EC No: 273-103-3	Polysulfides, di-tert-Bu	0.1 - 0.99 %	Aquatic Acute 1, H400 - Aquatic Chronic 2, H411 - Skin Sens. 1B, H317	-	
CAS No: 115-86-6 EC No: 204-112-2 Registration No: 01- 2119457432-41-XXXX	[1] triphenyl phosphate	0 - 0.249 %	Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 (M=1)	-	

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1 Date of compilation: 18/06/2019

Version 11 (replaces version 10) Revision date: 23/12/2021

Page 3 of 11 Print date: 23/12/2021

Index No: 607-035- 00-6 Image: Constant of the system CAS No: 80-62-6 [1] methyl methacrylate, methyl 2-methylprop-2- enoate, methyl 2-methylpropenoate EC No: 201-297-1 enoate, methyl 2-methylpropenoate Registration No: 01- 2119452498-28-XXXX Ender State	0 - 0.99 %	Flam. Liq. 2, H225 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 - STOT SE 3, H335	-
---	------------	--	---

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eve contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1 Date of compilation: 18/06/2019

Version 11 (replaces version 10) Revision date: 23/12/2021

Page 4 of 11 Print date: 23/12/2021

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Profesional use only. Automotive, Industry, Transport, Off-Highway Machinery.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
lubricating oils (petroleum), C20-50,	72623-87-1	España [1]	Eight hours		5

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1Date of compilation: 18/06/2019Version 11 (replaces version 10)Revision date: 23/12/2021

Page 5 of 11 Print date: 23/12/2021

hydrotreated neutral oil-based, Baseoil — unspecified, [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 oC. It contains a relatively large proportion of saturated hydrocarbons.]			Short term		10
distillates (petroleum), hydrotreated			Eight hours		5
light paraffinic, Baseoil — unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 oF (19cSt at 40 oC). It contains a relatively large proportion of saturated hydrocarbons.]	64742-55-8	España [1]	Short term		10
distillates (petroleum), solvent-dewaxed			Eight hours		5
heavy paraffinic, Baseoil — unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 oF (19cSt at 40 oC).]	64742-65-0	España [1]	Short term		10
		España [1]	Eight hours		3
			Short term		
		United	Eight hours		3
		Kingdom [2]	Short term		6
		Éire [3]	Eight hours		3
triphenyl phosphate	115-86-6		Short term		
		United States	Eight hours		3
		[4] (Cal/OSHA)	Short term		
		United States	Eight hours		3
		[5] (NIOSH)	Short term		
		United States	Eight hours		3
		[6] (OSHA)	Short term		
		España [1]	Eight hours	50(sensibilizante) 100(sensibilizant	
methyl methacrylate, methyl 2-	80-62-6		Short term	e)	
methylprop-2-enoate, methyl 2-	80-62-6	European	Fight hours	50	
methylprop-2-enoate, methyl 2- methylpropenoate	80-62-6	European	Eight hours	50	
	80-62-6	Union [7]	Short term	100	200
	80-62-6				208 416

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1 Date of compilation: 18/06/2019

Version 11 (replaces version 10) Revision date: 23/12/2021

Page 6 of 11 Print date: 23/12/2021

	Éire [2]	Eight hours	50	
	Éire [3]	Short term	100	
	United States	Eight hours	50	
	[4] (Cal/OSHA)	Short term	100	
		Eight hours	100	
		Short term		
	United States	Eight hours	100	410
	[6] (OSHA)	Short term		

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Sequridad y Salud en el Trabajo (INSST) para el año 2021.

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. [3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health,

Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100. [6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs),

California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[7] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and	DNEL	Inhalation, Long-term, Systemic effects	8,13
pentyl) esters, zinc salts	(Workers)		(mg/m³)
CAS No: 68457-79-4			
EC No: 270-608-0			
tris(methylphenyl) phosphate	DNEL	Inhalation, Long-term, Systemic effects	0,47
CAS No: 1330-78-5	(Workers)		(mg/m³)
EC No: 215-548-8			
triphenyl phosphate	DNEL	Inhalation, Long-term, Systemic effects	0,55
CAS No: 115-86-6	(Workers)		(mg/m³)
EC No: 204-112-2	. ,		
methyl methacrylate, methyl 2-methylprop-2-enoate,	DNEL	Inhalation, Long-term, Local effects	208
methyl 2-methylpropenoate	(Workers)	-	(mg/m³)
CAS No: 80-62-6	DNEL	Inhalation, Long-term, Systemic effects	208
EC No: 201-297-1	(Workers)		(mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable

minimum. Distillates (petroleum), solvent-dewaxed heavy parafinic

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Transmission oil
Breathing protecti	on:
If the recommended	technical measures are observed, no individual protection equipment is necessary.
Hand protection:	
If the product is han	dled correctly, no individual protection equipment is necessary.
Eye protection:	
If the product is han	dled correctly, no individual protection equipment is necessary.
Skin protection:	
PPE: Characteristics:	Work footwear. «CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347 This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should
Maintenance:	not be used by other people.

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1Date of compilation: 18/06/2019Version 11 (replaces version 10)Revision date: 23/12/2021

Page 7 of 11 Print date: 23/12/2021

Observations: Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour Colour: N.A./N.A. Odour:Suave Odour threshold:N.A./N.A. pH:N.A./N.A. Melting point:-30 °C Boiling Point: >300 °C Flash point: >220 °C Evaporation rate: N.A./N.A. Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A. Relative density:0.87 Solubility: Disolventes Petrolíferos Liposolubility: N.A./N.A. Hydrosolubility: < 0.1% Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A. N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A. Blink: N.A./N.A. Kinematic viscosity: 220 cSt a 40°C N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1Date of compilation: 18/06/2019Version 11 (replaces version 10)Revision date: 23/12/2021

Page 8 of 11 Print date: 23/12/2021

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

a) acute toxicity; Not conclusive data for classification.

b) skin corrosion/irritation; Based on available data, the classification criteria are not met.

c) serious eye damage/irritation; Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation; Based on available data, the classification criteria are not met.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Based on available data, the classification criteria are not met.

h) STOT-single exposure; Based on available data, the classification criteria are not met.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
Nalle	Log Pow	BCF	NOECs	Level
triphenyl phosphate	4,59	_	_	High
CAS No: 115-86-6 EC No: 204-112-2	7,35	-		riigh

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1 Date of compilation: 18/06/2019

Version 11 (replaces version 10) Revision date: 23/12/2021

Page 9 of 11 Print date: 23/12/2021

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

Waste classification according to the European Waste Catalogue:

13 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19)

13 02 waste engine, gear and lubricating oils

13 02 06 synthetic engine, gear and lubricating oils

Waste classified as hazardous.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

 Description:

 ADR:
 Not classified as hazardous for transport.

 IMDG:
 Not classified as hazardous for transport.

 ICAO/IATA:
 Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1Date of compilation: 18/06/2019Version 11 (replaces version 10)Revision date: 23/12/2021

Page 10 of 11 Print date: 23/12/2021

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

child.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2 Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3 Asp. Tox. 1 : Aspiration toxicity, Category 1 Eye Dam. 1 : Serious eye damage, Category 1 Flam. Liq. 2 : Flammable liquid, Category 2 Repr. 2 : Reproductive toxicant, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1B : Skin sensitiser, Category 1 Stort SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the first aid measures (SECTION 4.1).
- Modification in the firefighting measures (SECTION 5.3).
- Modifications in the accidental release measures (SECTION 6.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Elimination of exposure data (SECTION 8.1).
- Addition of exposure data (SECTION 8.1).
- Change in the hazard classification (SECTION 11.1).
- Addition of ecological information values (SECTION 12.3).
- Addition of abbreviations and acronyms (SECTION 16).

(in accordance with Regulation (EU) 2015/830)

MAXIGEAR SYN 220



Version 1Date of compilation: 18/06/2019Version 11 (replaces version 10)Revision date: 23/12/2021

Page 11 of 11 Print date: 23/12/2021

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data Health hazards Calculation method Environmental hazards Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- Log Pow: Logarithm of the partition octanol-water.
- NOEC: No observed effect concentration.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.