(in accordance with Regulation (EU) 2015/830)

# **OLICUT 515**

Version: 4 Revision date: 18/09/2018



Page 1 of 8 Print date: 18/09/2018

## SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

Product Name:

1.1 Product identifier.

OLICUT 515

**1.2** Relevant identified uses of the mixture and uses advised against.

Metalworking fluid

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	OLIPES SL
Address:	C/ ALUMINIO, 2-3 (Parque Empresarial Borondo)
City:	Campo Real - 28510
Province:	Madrid (Spain)
Telephone:	+0034918765244
Fax:	+0034918733886
E-mail:	calidad@olipes.com
Web:	www.olipes.com

1.4 Emergency telephone number: (Only available during office hours; Monday-Friday; 08:00-18:00)

# **SECTION 2: HAZARDS IDENTIFICATION.**

### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008: Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

## 2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008: Pictograms:

H statements: H412 Harmful to aquatic life with long lasting effects.

 P statements:
 P273
 Avoid release to the environment.

 P501
 Dispose of contents/container in accordance with the legislation in force.

EUH statements: EUH208

Contains N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine. May produce an allergic reaction.

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

(in accordance with Regulation (EU) 2015/830)

# **OLICUT 515**

## Version: 4

## Revision date: 18/09/2018

**Olipes** The Professionals' Lubricants

> Page 2 of 8 Print date: 18/09/2018

Not Applicable.

## 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
Identifiers			Classification	specific concentration limit
CAS No: 1330-78-5 EC No: 215-548-8 Registration No: 01- 2119531335-46-XXXX	tris(methylphenyl) phosphate	0.25 - 2.49 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Repr. 2, H361fd	-
CAS No: 80584-90-3 EC No: 279-503-4	N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole- 1-methylamine	0.1 - 0.99 %	Aquatic Chronic 2, H411 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 115-86-6 EC No: 204-112-2 Registration No: 01- 2119457432-41-XXXX	[1] triphenyl phosphate	0 - 0.249 %	Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 (M=1)	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

# **SECTION 4: FIRST AID MEASURES.**

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

## Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

# **SECTION 5: FIREFIGHTING MEASURES.**

The product is NOT classified as flammable, in case of fire the following measures should be taken:

## 5.1 Extinguishing media.

(in accordance with Regulation (EU) 2015/830)

# OLICUT 515

Version: 4

## Revision date: 18/09/2018

Page 3 of 8

The Professionals' Lubricants

lipes

Print date: 18/09/2018

#### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### 5.2 Special hazards arising from the mixture.

### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

#### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

## 6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

#### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the around.

#### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

## **SECTION 7: HANDLING AND STORAGE.**

### 7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

#### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

## 7.3 Specific end use(s).

Professional use only.

(in accordance with Regulation (EU) 2015/830)

# **OLICUT 515**

Version: 4

Revision date: 18/09/2018

**Olipes** The Professionals' Lubricants

> Page 4 of 8 Print date: 18/09/2018

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

## 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
	115-86-6	España [1]	Eight hours		3
triphonyl phocphata			Short term		
triphenyl phosphate		United	Eight hours		3
		Kingdom [2]	Short term		6

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT) para el año 2017.

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
tris(methylphenyl) phosphate	DNEL	Inhalation, Long-term, Systemic effects	0,47
CAS No: 1330-78-5	(Workers)		(mg/m <sup>3</sup> )
EC No: 215-548-8			
triphenyl phosphate	DNEL	Inhalation, Long-term, Systemic effects	0,55
CAS No: 115-86-6	(Workers)		(mg/m <sup>3</sup> )
EC No: 204-112-2			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

### 8.2 Exposure controls.

### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:	Metalworking fluid			
<b>Breathing protecti</b>	Breathing protection:			
If the recommended	technical measures are observed, no individual protection equipment is necessary.			
Hand protection:				
If the product is hand	dled correctly, no individual protection equipment is necessary.			
Eye protection:				
If the product is hand	dled correctly, no individual protection equipment is necessary.			
Skin protection:	Skin protection:			
PPE:	Work footwear.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN ISO 13287, EN 20347			
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.			
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident			

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

## 9.1 Information on basic physical and chemical properties.

Appearance:Liquid with characteristic odour Colour: N.A./N.A. Odour:N.A./N.A. Odour threshold:N.A./N.A. pH:N.A./N.A. Melting point:N.A./N.A.

(in accordance with Regulation (EU) 2015/830)

# **OLICUT 515**

Version: 4 Revision date: 18/09/2018



Page 5 of 8 Print date: 18/09/2018

Boiling Point: >250 °C Flash point: >250 °C Evaporation rate: N.A./N.A. Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density:N.A./N.A. Relative density:0.917 Solubility:Oil solvents Liposolubility: N.A./N.A. Hydrosolubility: Insoluble Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A. Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A. N.A./N.A. = Not Available/Not Applicable due to the nature of the product

## 9.2 Other information.

Dropping point: N.A./N.A. Blink: N.A./N.A. Kinematic viscosity: 35 a 40°C N.A./N.A.= Not Available/Not Applicable due to the nature of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### **10.6** Hazardous decomposition products.

No decomposition if used for the intended uses.

# SECTION 11: TOXICOLOGICAL INFORMATION.

## **11.1 Information on toxicological effects.**

There are no tested data available on the product. Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

## a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation; Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Not conclusive data for classification.

(in accordance with Regulation (EU) 2015/830)

# **OLICUT 515**

Version: 4 Revision date: 18/09/2018



Page 6 of 8 Print date: 18/09/2018

d) respiratory or skin sensitisation; Based on available data, the classification criteria are not met.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Based on available data, the classification criteria are not met.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

# SECTION 12: ECOLOGICAL INFORMATION.

## 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

## 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present.No information is available about persistence and degradability of the product.

## 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
Name	Log Pow	BCF	NOECs	Level
triphenyl phosphate	4 50			High
CAS No: 115-86-6 EC No: 204-112-2	4,59	-	-	High

## 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

## 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

## 12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

# SECTION 13 DISPOSAL CONSIDERATIONS.

## 13.1 Waste treatment methods.

(in accordance with Regulation (EU) 2015/830)

# **OLICUT 515**

**Olipes** The Professionals' Lubricants

Version: 4 Revision date: 18/09/2018 Page 7 of 8 Print date: 18/09/2018

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

Waste classification according to the European Waste Catalogue:

12 WASTES FROM SHAPING AND PHYSICAL AND MECHANICAL SURFACE TREATMENT OF METALS AND PLASTICS

12 01 wastes from shaping and physical and mechanical surface treatment of metals and plastics

12 01 07 mineral-based machining oils free of halogens (except emulsions and solutions)

Waste classified as hazardous.

# SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6. **14.1 UN number.** 

Transportation is not dangerous.

## 14.2 UN proper shipping name.

Description: ADR: Transportation is not dangerous. IMDG: Transportation is not dangerous. ICAO/IATA: Transportation is not dangerous.

## 14.3 Transport hazard class(es).

Transportation is not dangerous.

### 14.4 Packing group.

Transportation is not dangerous.

## 14.5 Environmental hazards.

Transportation is not dangerous.

### 14.6 Special precautions for user.

Transportation is not dangerous.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

## **SECTION 15: REGULATORY INFORMATION.**

## 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H315 Causes skin irritation.

(in accordance with Regulation (EU) 2015/830)

# **OLICUT 515**

Version: 4 Revision date: 18/09/2018



Page 8 of 8 Print date: 18/09/2018

H317	May cause an allergic skin reaction.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2 Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3 Repr. 2 : Reproductive toxicant, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

Sections changed compared with the previous version:

1,3,8,14,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be
- considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- Log Pow: Logarithm of the partition octanol-water.
- NOEC: No observed effect concentration.
- NOLC. NO Observed effect concentrat

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2015/830. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.