

STARTWIN 2T SYNTHETIC

DESCRIPTION:

Synthetic lubricating oil especially developed for two-stroke motors for city driving where low smoke emissions are required.

PROPERTIES AND ADVANTAGES:

It exceeds the most modern requirements for two-stroke motors from manufacturers: lubricity, piston wear, detergency, and, above all, smoke formation, perfect for urban duty cycles.

Avoids the contamination of hot components in the engine due to its power detergent action.

Maximum protection against wear, prolonging engine life.

Complete and perfect miscibility with both leaded and unleaded petrol.

Thanks to its low ash content and high dispersing power, it avoids the problem of spark plug glazing and minimises the formation of deposits on pistons and at ports.

High anti-oxidant and anti-corrosion protection of the lubricated elements.

APPLICATIONS:

Two-stroke engines, motorbikes, scooters.

Garden machinery, chainsaws, lawnmowers, generating sets.

SPECIFICATIONS / QUALITY LEVEL:

API TC
ISO-L-EGD
JASO FD

TECHNICAL DATA:

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
Density at 15 °C, typical	ASTM D-1298	0.870
Color	VISUAL	red
Viscosity, cSt. 100°C	ASTM D-445	10 - 12
Pour point (°C) (F°), max.	ASTM D-97	-20

REMARKS:

Mix with petrol in the proportions recommended by the manufacturer of the engine.

PACKAGING:

1L bottle, 20L jerrycan and 200L drum