

FLOW DES P

DESCRIPTION:

Release agent, formulated with a balanced blend of highly-refined paraffin bases, antioxidant additives, polar-bonded additives, and unctuousness agents.

APPLICATIONS:

- ✓ Release agent for direct use.
- ✓ Formwork moulds used in works.
- ✓ Release agent for concrete joists.
- ✓ Prefabricated concrete.

PROPERTIES & ADVANTAGES:

- ✓ Due to its polarity, it forms an even layer on the moulds, achieving an excellent surface finish.
- ✓ It avoids concrete adhering to the metal moulds, making it easier to clean them, extending their useful service life.
- ✓ It does not stain or penetrate the concrete.
- ✓ It reduces the risk of pieces fracturing during release, as well as the tendency to form imperfections, improving the appearance of the released surfaces.
- ✓ It ensures that the wood used during release lasts longer, avoiding deformation or splintering.

TECHNICAL DATA:

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
Viscosity at 40 °C (cSt)	ASTM D-445	7 - 15
Density at 15 °C, kg/l	ASTM D-1298	0.850 - 0.860
Flash point (°C)	ASTM D-92	> 100
Pour point (°C)	ASTM D-97	-10

HOW TO USE:

- ✓ Direct use, non-emulsifiable product.
- ✓ Can be applied with a brush, roller, spray gun, sponge, or by dipping.

PACKAGING:

20 L jerry can and 200 L drum.