

MAXICER 20W40 TD (Super Serie III)

DESCRIPTION:

Lubricating oil for diesel and petrol engines, formulated with highly-refined mineral bases and additives with a strong detergent, anti-wear, dispersant, and anti-corrosion action.

APPLICATIONS:

- ✓ Petrol engines with or without a catalytic converter.
- ✓ Fleets of mixed vehicles with diesel engines that require API CD quality level.
- ✓ Industrial vehicles, lorries, vans, and tractors, fishing vessels.

PROPERTIES & ADVANTAGES:

- ✓ Thanks to its light multi-grade properties it enables start-up at low temperatures and maintains pressure at high temperatures, improving the lubrication of engine components.
- ✓ High anti-wear protection of the lubricated elements.
- ✓ High dispersant and detergent ability, avoids cold build-up of sludge, sections sticking, blockages, and clogging of filters.
- ✓ Reduces oil consumption and prolongs the operating life of the engine.

SPECIFICATIONS / QUALITY LEVEL:

API CD / SF
MIL-L-46152B
MIL-L-2104D

TECHNICAL DATA:

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
SAE grade	SAE J300	20W40
Viscosity at 100 °C (cSt)	ASTM D-445	12.5 - 16.3
Density at 15 °C, Typical (kg/l)	ASTM D-1298	0.875
Dynamic viscosity -15 °C (cPs)	ASTM D-5293	< 9500
Pour point (°C)	ASTM D-97	< -15
Flash point (°C)	ASTM D-92	> 210

PACKAGING:

20L jerrycan, 200L drum, and 1000L IBC container.