

HEADQUARTERS - FACTORY

P. E. Borondo – Aluminio 2-3 28510 Campo Real (Madrid) - Spain

ESPAÑA - PORTUGAL:

○ 0034 918 765 244 **○** 0034 918 733 886

@ comercial@olipes.com

@ clientes@olipes.com

OTHER COUNTRIES:

0034 918 765 603 0034 918 733 886

@ export@olipes.com

@ exportation@olipes.com

ACEITE MOTOSIERRAS BBO CHAINSAW OIL BBO

DESCRIPTION:

High-performance lubricating oil, organic and biodegradable, exceeding 80% biodegradability in the CEC L-33-A-93 test.

APPLICATIONS:

- ✓ Specially formulated to lubricate chains on all chainsaws and similar equipment.
- ✓ General greasing of gardening, farming, and construction machinery.

PROPERTIES & ADVANTAGES:

- ✓ Its high adhesive power makes it resistant to the destruction of the oil film on adjoining surfaces whilst aiding the performance of cutting functions.
- ✓ Its biodegradable nature helps to preserve the environment, thus avoiding its contamination.
- ✓ Excellent performance. Reduced consumption.
- ✓ Excellent protection against rust and corrosion.
- ✓ High viscosity index, reducing variations in the viscosity caused by changes in temperature.
- ✓ It offers reduced consumption of oil lost to leaks and splashes.
- ✓ Excellent anti-wear capability, extending the useful life of the cutting chain.

TECHNICAL DATA

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
Colour	Visual	Light Green
Density at 15 °C, typical (kg/l)	ASTM D-1298	0.910 – 0.920
Viscosity at 100 °C (cSt)	ASTM D-445	10 – 14
Pour point (°C)	ASTM D-97	< -20
Flash point COC (°C)	ASTM D-92	> 250

PACKAGING:

5L bottle, 200L drum, and 1000L IBC container.