

HEADQUARTERS - FACTORY

P. E. Borondo – Aluminio 2-3 28510 Campo Real (Madrid) - Spain

ESPAÑA - PORTUGAL:

○ 0034 918 765 244 **○** 0034 918 733 886

@ comercial@olipes.com @ clientes@olipes.com OTHER COUNTRIES:

○ 0034 918 765 603 **○** 0034 918 733 886

@ export@olipes.com@ exportation@olipes.com

MASTERCLEAN HP-1

DESCRIPTION:

Special degreaser for the food industry, category H1, for applications with accidental contact with foodstuffs. Functions as a universal degreaser, removing remnants of oils, greases, and similar products in the foodstuffs industry quickly and easily.

PROPERTIES AND ADVANTAGES

- ✓ Free from halogen compounds, polynuclear aromatics, and PCBs.
- ✓ Free from substances harmful to human health.
- ✓ High solvent capacity.
- ✓ High flash point, ensuring safety during handling.
- ✓ Good evaporation rate.
- ✓ Inoffensive smell.
- ✓ Excellent dielectric capability

APPLICATIONS

- ✓ Cleaning remnants of grease and oil.
- ✓ Degreaser for metal mechanical parts.
- ✓ Interior cleaning of thermal fluid circuits, easily dissolving sludge and impurities sticking to surfaces.
- ✓ As a cleaning agent for mechanisms involved in the wider food industry: bushings, bearings, guides, carrier chains.

HOMOLOGATIONS:

Category Code H1

 $NSF\ Registration\ N^o:\ 160964$

HALAL License No.: IH-986/2.4/M/60

Contact us: +34 957 634 071





TECHNICAL DATA

PHYSICAL-CHEMICAL PROPERTIES	SPECIFICATION	VALUE
Appearance	Visual	Transparent and colourless liquid
Saybolt Colour, min.	ASTM D 156-87	30
Density at 15 °C (kg/l)	ASTM D-1298	0.76 – 0.78
Flash point , Min. (°C)	ASTM D-93	> 60
Kinematic viscosity at 20 °C (cSt)	ASTM D-445	1.30 – 5.50
Kinematic viscosity at 40 °C (cSt)	ASTM D-445	1.70
Odour content, Max. weight (%)	UOP 495-75	0.1

PRESENTATION:

20 L bottles.

