

STARTWIN 2T SPECIAL

DESCRIPTION:

Synthetic lubricating oil especially for air-cooled two-stroke motors with oil-petrol mixture lubrication systems.

PROPERTIES & ADVANTAGES:

- ✓ Complete and rapid miscibility with petrol.
- ✓ Increases the power of the motor.
- ✓ Makes ignition easier.
- ✓ Eliminates spark plug glazing.
- ✓ Its high detergent power suppresses sooty residues, keeping the piston rings and ports clean.
- ✓ Reduces smoke emissions.
- ✓ Saves fuel.
- ✓ Maximum anti-wear and anti-seize.

APPLICATIONS:

- ✓ Recommended for mopeds, motorcycles, chainsaws, devices fitted with two-stroke motors, etc.

SPECIFICATIONS / QUALITY LEVEL:

API TC	JASO FC	ISO-L-EGD
--------	---------	-----------

TECHNICAL DATA:

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
Colour	Visual	Green
Viscosity at 100 °C (cSt)	ASTM D-445	8.0 - 11.0
Density at 15 °C, Typical (kg/l)	ASTM D-1298	0.870
Pour point (°C)	ASTM D-97	< -20
Flash point (°C)	ASTM D-92	> 200

HOW TO USE:

Mix with fuel in the proportions recommended by the manufacturer of the vehicle.

PACKAGING:

125 cc tubes