
OLIBAT 22 LU

DESCRIPTION:

A high quality pure lube oil, with high performance, specially formulated for deep drawing and stamping operations. It contains additives for extreme pressure, sulpho-chlorinated, anticorrosive and antioxidant ingredients. Water-soluble.

PROPERTIES & ADVANTAGES:

- ✓ High content of additives, high lubrication factor and unctuousness, thus reducing friction.
- ✓ It facilitates stamping and deep drawing operations in hard steel and stainless steel plates.
- ✓ Great quality of finish, avoiding scratches and welding between spare parts, hence, increasing their useful life.
- ✓ Good antioxidant protection on machined parts.
- ✓ Suitable for lubrication of guides.

APPLICATIONS:

- ✓ Cold deep drawing and stamping of stainless steel plates and hard steel in medium and high complexity mechanical operations.
- ✓ It can be applied with a roller, spray, brush, etc.

TECHNICAL DATA:

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
Density at 15 °C (Kg/L)	ASTM D-1298	0.915 – 0.930
Viscosity at 40 °C (cSt)	ASTM D-445	60 – 75
Flash point (°C)	ASTM D-92	> 210

PACKAGING:

20L jerrycan and 200L drum.