

## OLICUT GLASS

### DESCRIPTION:

Vanishing lubricating oil for glass cutting. Free from aromatic products, respectful with the environment.

### PROPERTIES & ADVANTAGES:

- High flash point, improves the safety of the operation.
- Provides an excellent surface finish.
- Quick evaporation, minimizing residue on the tool and the finished part.
- Its specific composition softens contact with the skin.
- Does not generate unpleasant fumes or odors during the cutting process.

### TECHNICAL DATA:

| <u>PHYSICOCHEMICAL CHARACTERISTICS</u> | <u>STANDARD</u>   | <u>VALUE</u>                |
|--|-------------------|-----------------------------|
| NATURE .....                           | -----             | PETROLEUM                   |
| DENSITY AT 15°C .....                  | ASTM D-1298 ..... | 0.780 – 0.800               |
| COLOUR .....                           | ASTM D-1500 ..... | ≤ 0.5                       |
| VISCOSITY cSt. 40°C .....              | ASTM D-445 .....  | 1.8 – 2.0                   |
| FLASH POINT, °C, Min .....             | ASTM D-92 .....   | 70                          |
| POUR POINT, °C, Max .....              | ASTM D-97 .....   | -50                         |
| EVAPORATION RATE .....                 | DIN 53170 .....   | 800 (DiethylEther = 1)      |
|  | ASTM D-3539 ..... | 0.01 (n-n-ButylAcetate = 1) |

### APPLICATIONS:

Cutting, drilling, polishing and glass beveling operations.

### PACKAGING:

200L drum