

HEADQUARTERS – FACTORY P. E. Borondo – Aluminio 2-3 28510 Campo Real (Madrid) - Spain

ESPAÑA - PORTUGAL:

**○** 0034 918 765 244 **○** 0034 918 733 886

@ comercial@olipes.com

@ clientes@olipes.com

33 886

OTHER COUNTRIES: 0034 918 765 603 0034 918 733 886

@ export@olipes.com @ exportation@olipes.com

VISCOFLOW 300 (LONG - LIFE)

#### **DESCRIPTION:**

Honey-colored lubricant fluid, formulated for the lubrication of all types of chains, particularly recommended for ROLAND machinery.

# **PROPERTIES & ADVANTAGES:**

- ✓ Excellent adhesion.
- ✓ Excellent protection against corrosion.
- ✓ Extreme capacity to withstand powerful continuous and impact loads.
- ✓ Resistant in aggressive environments (exposure to the sun, moisture, dust, vibration)
- ✓ Easily pumped.
- ✓ Resistant to hot and cold water.
- ✓ Long-Life.
- ✓ Excellent anti-aging power.

#### **APPLICATIONS:**

Special highly adherent oil for chains.

### **TECHNICAL DATA:**

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
Color		YELLOW
Viscosity cSt 100 °C, standard.	ASTM D-445	300
Pour point, max. ºC	ASTM D-97	-30
4-ball EP test, nw	DIN 51350	5500
Timken load, lbs	F.T.M.S. 791 MET. 6505	60
Water resistance +90 °C	DIN 51807	RESISTANT
Protection against corrosion	DIN 51802	LEVEL 0
Protection against oxidation (100 hours at 100 °C), bar	DIN 51808	0.5
FZG, pass	DIN 51354	13

## **PACKAGING:**

1-litre and 5-litre bottles and 50-litre drums.

0409