

## FLOW DES I/2003

### DESCRIPTION:

Very fluid petroleum release agent with a paraffinic structure for direct use. Endowed with antioxidant, polar and unctuous additives.

### ADVANTAGES / PROPERTIES:

- ✓ Due to its adherence, it forms a thin film on the molds that allows effective protection against corrosion and a correct finish.
- ✓ DOES NOT STAIN. Does not attack molds nor does it penetrate into the concrete.
- ✓ Reduces the risk of breakage of pieces in the stripping, as well as the tendency to the formation of holes, improving the appearance of the stripped surfaces.
- ✓ Ensures a longer duration of the wood in stripping, avoiding its deformation and splintering.
- ✓ Prevents the adherence of the concrete to the molds, thereby facilitating their cleaning and increasing their duration

### APPLICATIONS

- ✓ Immediate release agent in all types of prefabricated concrete, beams, posts, medians, pillars, etc.
- ✓ Stripping of light-colored prefabricated artificial stone and any material where an excellent "stainless" final finish is required.

### TECHNICAL DATA:

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
Color	Visual	Colorless
Viscosity at 40°C, cSt	ASTM D-445	1,9-3,0
Density at 15°C	ASTM D-2896	0,800-0,830
Freezing Point (°C), max.	ASTM D-97	-20
Flash Point (°C), min.	ASTM D-92	100

### FORM OF EMPLOYMENT:

- ✓ Direct use, non-emulsifiable.
- ✓ Applicable with a brush, spray gun, sponge or immersion.

### PACKAGING

20L jerrycan, 200 L Drums and 1,000 L Containers