

MAXIGEAR TS 4800

Pg. 1 / 2

DESCRIPTION:

Lubricant oil, SAE Grade 75W90, for high performance gearing. Formulated with synthetic bases and cutting-edge additives.

APPLICATIONS:

- ✓ Especially designed to lubricate manual transmissions and synchronizes gearboxes, hypoid drive shafts, differentials groups, and transfer cases.
- ✓ Gear systems which require API GL4 / GL5 quality.
- ✓ Gearing subjected to high torque or high rotational speeds.
- ✓ Heavy construction equipment, coaches, urban buses, heavy transport, private and commercial vehicles, forklifts, tractors, and combine harvesters.

PROPERTIES AND ADVANTAGES:

- ✓ It provides excellent load-bearing capability, considerably reducing losses to friction.
- ✓ It allows extended drain intervals thanks to its synthetic formulation.
 - From 500 hours up to 1500 hours according to the working conditions and type of load.
 - Up to 120,000 km in manual gearboxes on private and commercial vehicles.
 - Up to 150,000 km in heavy transport on public roads.
- ✓ Formulated with components with high shear stability, maintaining its initial viscosity and ensuring an adequate lubricating film on the metallic surface of the gears.
- ✓ Excellent resistance to thermal degradation.
- ✓ High lubricity and anti-wear protection.
- ✓ Outstanding fluidity at low temperature, reducing premature wear caused by starts at cold.
- ✓ Reduced formation of deposits, keeping the gears in an optimal state of cleanliness.
- ✓ Improved anti-corrosive properties, excellent anti-rust protection.
- ✓ It improves the performance of gears and bearings.

SPECIFICATIONS: (*)

API GL4 / GL4 + / GL5 / MT1	MACK GO J & J PLUS
EATON 2834	MAN 342 S1, S2
Fiat 9.55550-MX4 / Fiat 9.55550-DA6 & DA7	MAN 3343 S
FORD WSD-M2C-200C	SCANIA STO 1:0
IVECO 1805 Class RAS1	VOLVO / RENAULT / MACK 97310
ZF TE ML 05A / 05B / 07A / 16F / 17A / 17B / 19C / 21A / 21B	

(*) *Suitable for Use (SFU)*

MAXIGEAR TS 4800

Pg. 2 / 2

Compatible with 80W90 formulations where the following specifications are required:

API GL4 / GL5 / MT1	MIL-PRF-2105E
MAN 341 Z2	SAE J2360
MB 235.6	RENAULT VI Standard N 03-08-4003
MIL-L-2105D	

Compatible with 80W90 formulations where required:

Opel-Vauxhall manual Transmission Fluid, Part No. 93165290

TECHNICAL DATA

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	VALUE
SAE grade	SAE J-306	75W90
Viscosity at 100°C (cSt)	ASTM D-445	13.5 - 18.0
Viscosity at -40°C, Max. (cP)	ASTM D-2983	150,000
Density at 15°C, typical (kg/l)	ASTM D-1298	0.875
Pour point, Max. (°C)	ASTM D-97	-40
Flash point (°C)	ASTM D-92	180
Wear test, impact at high speed	CRC L-42	Passes
Wear test, low speed - high torque	CRC L-37	Passes
Stability against oxidation	CRC L-60	Passes

PACKAGING:

20L jerry can and 200L drum.