

HEADQUARTERS - FACTORY

P. E. Borondo – Aluminio 2-3 28510 Campo Real (Madrid) - Spain

ESPAÑA - PORTUGAL:

○ 0034 918 765 244 ○ 0034 918 733 886

@ comercial@olipes.com@ clientes@olipes.com

OTHER COUNTRIES:

○ 0034 918 765 603 **○** 0034 918 733 886

@ export@olipes.com@ exportation@olipes.com

OLIBLANC M

DESCRIPTION:

Colorless medicinal white oil which is odorless, tasteless, transparent and free of any unsaturated hydrocarbons, whether linear or branched, cyclical and polycyclic (polynuclear).

Other designations generally used in addition to white oil are: liquid vaseline, vaseline oil, liquid paraffin.

APPLICATIONS:

White oils are reliable, irreplaceable products in a wide range of applications in activities developed by the food, pharmaceutical and cosmetic industry:

- Machines and mechanisms which may accidentally come into contact with food.
- Plasticizer in processing industries involving plastics, rubbers and specific containers for use in cosmetics, pharmacy and food.
- · Antifoaming.
- Separating agent for dough processing and baking products, sifting rice.
- Master formulas. Suntan creams and lotions in a wide range of cosmetic preparations.
- Diluent, dispersant, softener, antifoaming agent...
- Thermal fluids on heating circuits in food industries (maximum working temperature 320°C in a closed circuit and in the absence of oxygen and/or humidity).
- General greasing of machinery.
- Uses requiring an oil with a high dielectric capacity.

SPECIFICATIONS & ADVANTAGES:

Complies with 21 CFR 172.878 of the FDA regulated as a food additive for direct addition to foodstuffs intended for human consumption.

Complies with pharmacopoeias: USP XXII, DAB 10, BP 93, CODEX 1990, Eur pH II.

APPROVALS:

Code H1 Category ISO 21469:2006. N°: K-0219680/1 License HALAL n° IH-986/2.4/M/60 Contact us: +34 957 634 071





TECHNICAL DATA:

PHYSICOCHEMICAL CHARACTERISTICS	STANDARD	M-2	M-5
Density at 15°C, g/ml	ASTM D-1298	0.845	0.865
Viscosity at 40 °C, cSt	ASTM D-445	22	68
Flashpoint (C.O.C.),	ASTM D-92	208	220
Pour point, °C, Max	ASTM D-97	-9	-9
U.V. absorption (F.D.A.)	CFR 172.878	Compliant	Compliant
NSF Registration N°	-	141984	170132

Note: These data represent average values after different tests. Given the wide variety of operating conditions, they do not constitute a basis for specifications. Olipes SL reserves the right to modify the indicated data without prior notice.

PACKAGING:

20L jerrycan, 200L drum and 1,000L IBC container.

