

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 1 of 14

Print date: 10/05/2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: MASTERCLEAN CAR BBO

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Degreaser

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **OLIPES SL**
Address: C/ ALUMINIO, 2-3 (Parque Empresarial Borondo)
City: Campo Real - 28510
Province: Madrid (Spain)
Telephone: +0034918765244
Fax: +0034918733886
E-mail: calidad@olipes.com
Web: www.olipes.com

1.4 Emergency telephone number: (Only available during office hours; Monday-Friday; 08:00-18:00)

Servicio de Información Toxicológica (Instituto Nacional de Toxicología y Ciencias Forenses) Teléfono: +34 91 5620420.

Información en español (24h/365 días). Únicamente con la finalidad de proporcionar respuesta sanitaria en caso de urgencia.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Eye Dam. 1 : Causes serious eye damage.

Skin Irrit. 2 : Causes skin irritation.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H315 Causes skin irritation.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.

P statements:

P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 2 of 14

Print date: 10/05/2021

P310	Immediately call a POISON CENTER or a doctor.
P321	Specific treatment (if possible visit your doctor with the safety data sheet for this product).
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with the legislation in force.

Contains:
tetrasodium ethylene diamine tetraacetate
Alcohol,C12-15, ethoxylated
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
: 603-014-00-0 : 111-76-2 : 203-905-0 : 01-2119475108-36-XXXX	[1] 2-butoxyethanol, ethyleneglycol monobutyl ether, butyl cellosolve	1 - 9.99 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Acute Tox. 4 *, H302 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315	-
: 603-117-00-0 : 67-63-0 : 200-661-7 : 01-2119457558-25-XXXX	[1] propan-2-ol, isopropyl alcohol, isopropanol	1 - 9.99 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
: 68411-30-3 : 270-115-0 : 01-2119489428-22-XXXX	Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts	3 - 9.99 %	Acute Tox. 4, H302 - Aquatic Chronic 3, H412 - Eye Dam. 1, H318 - Skin Irrit. 2, H315	Acute Tox. 4, H302: C ≥ 65 %
: 607-428-00-2 : 64-02-8 : 200-573-9 : 01-2119486762-27-XXXX	tetrasodium ethylene diamine tetraacetate	1 - 2.99 %	Acute Tox. 4, H332 - Eye Dam. 1, H318 - Met. Corr. 1, H290 - Skin Irrit. 2, H315	-
: 68131-39-5 : 500-195-7 : 01-2119488720-33-XXXX	Alcohol,C12-15, ethoxylated	1 - 2.99 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 - Eye Dam. 1, H318	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 3 of 14

Print date: 10/05/2021

: 603-030-00-8 : 141-43-5 : 205-483-3 : 01-2119486455-28-XXXX	[1] 2-aminoethanol, ethanolamine	0 - 0.99 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Acute Tox. 4 *, H302 - Skin Corr. 1B, H314	STOT SE 3, H335: C ≥ 5 %
: 96690-44-7 : 306-238-4	Quaternary ammonium compounds, C12-14-alkyltrimethyl, Me sulfates	0.1 - 0.99 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 (M=1) - Eye Dam. 1, H318 - Skin Corr. 1B, H314	-
: 01-2119962190-43	Aminas, N-alkil- de sebo trimetilendi-,etoxiladas	0.25 - 0.99 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Dam. 1, H318 - Skin Corr. 1B, H314 - STOT RE 1, H372	-
: 011-002-00-6 : 1310-73-2 : 215-185-5 : 01-2119457892-27-XXXX	[1] sodium hydroxide, caustic soda	0 - 0.499 %	Eye Dam. 1, H318 - Met. Corr. 1, H290 - Skin Corr. 1A, H314	Skin Corr. 1A, H314: C ≥ 5 % Skin Corr. 1B, H314: 2 % ≤ C < 5 % Skin Irrit. 2, H315: 0,5 % ≤ C < 2 % Eye Irrit. 2, H319: 0,5 % ≤ C < 2 %

(* The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 4 of 14

Print date: 10/05/2021

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.
Contact with eyes may cause irreversible damage.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 5 of 14

Print date: 10/05/2021

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Professional use only. Automotive, Industry, Transport, Off-Highway Machinery.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
2-butoxyethanol, ethyleneglycol monobutyl ether, butyl cellosolve	111-76-2	España [1]	Eight hours	20	98
			Short term	50	245
		European Union [2]	Eight hours	20 (skin)	98 (skin)
			Short term	50 (skin)	246 (skin)
		United Kingdom [3]	Eight hours	25	123
			Short term	50	246
		Éire [4]	Eight hours	20	98
			Short term	50	246
		United States [5] (Cal/OSHA)	Eight hours	20	
			Short term		
		United States [6] (NIOSH)	Eight hours	5	
			Short term		
		United States [7] (OSHA)	Eight hours	50	240
			Short term		
propan-2-ol, isopropyl alcohol, isopropanol	67-63-0	España [1]	Eight hours	200	500
			Short term	400	1000
		United Kingdom [3]	Eight hours	400	999
			Short term	500	1250
		Éire [4]	Eight hours	200	
			Short term	400	
		United States [5] (Cal/OSHA)	Eight hours	400	
			Short term	500	
		United States [6] (NIOSH)	Eight hours	400	
			Short term	500	
United States [7] (OSHA)	Eight hours	400	980		
	Short term				
2-aminoethanol, ethanolamine	141-43-5	España [1]	Eight hours	1	2,5
			Short term	3	7,5
		European Union [2]	Eight hours	1 (skin)	2,5 (skin)
			Short term	3 (skin)	7,6 (skin)
		United Kingdom [3]	Eight hours	1	2,5
			Short term	3	7,6
		Éire [4]	Eight hours	1	2,5
			Short term	3	7,6

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021
Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 6 of 14
Print date: 10/05/2021

		United States [5] (Cal/OSHA)	Eight hours	3	
			Short term	6	
		United States [6] (NIOSH)	Eight hours	3	6
			Short term		
		United States [7] (OSHA)	Eight hours	3	
			Short term	6	
sodium hydroxide, caustic soda	1310-73-2	España [1]	Eight hours		
			Short term		2
		United Kingdom [3]	Eight hours		
			Short term		2
		Éire [4]	Eight hours		
			Short term		2
		United States [5] (Cal/OSHA)	Eight hours	(Ceiling) 2	
			Short term		
		United States [6] (NIOSH)	Eight hours		(Ceiling) 2
			Short term		
		United States [7] (OSHA)	Eight hours		2
			Short term		

Biological exposure limit values for:

Name	CAS No.	Country	Biological indicator	BLV	Sampling time
2-butoxyethanol, ethyleneglycol monobutyl ether, butyl cellosolve	111-76-2	España [1]	Acido butoixacético en orina	200 mg/g creatinina	Final de la jornada laboral
propan-2-ol, isopropyl alcohol, isopropanol	67-63-0	España [1]	Acetona en orina	40 mg/l	Final de la semana laboral

[1] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad y Salud en el Trabajo (INSST) para el año 2018.

[2] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[3] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[4] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[5] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[6] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[7] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
2-butoxyethanol, ethyleneglycol monobutyl ether, butyl cellosolve CAS No: 111-76-2 EC No: 203-905-0	DNEL (Workers)	Inhalation, Long-term, Systemic effects	98 (mg/m ³)
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	500 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	89 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	888 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	319 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	26 (mg/kg bw/day)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 7 of 14

Print date: 10/05/2021

Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No: 68411-30-3 EC No: 270-115-0	DNEL (Workers)	Inhalation, Long-term, Local effects	12 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	12 (mg/m ³)
Alcohol, C12-15, ethoxylated CAS No: 68131-39-5 EC No: 500-195-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	294 (mg/m ³)
2-aminoethanol, ethanolamine CAS No: 141-43-5 EC No: 205-483-3	DNEL (Workers)	Inhalation, Long-term, Local effects	3,3 (mg/m ³)
sodium hydroxide, caustic soda CAS No: 1310-73-2 EC No: 215-185-5	DNEL (Workers)	Inhalation, Long-term, Local effects	1 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	1 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	aqua (freshwater)	140,9 (mg/L)
	aqua (marine water)	140,9 (mg/L)
	aqua (intermittent releases)	140,9 (mg/L)
	sediment (freshwater)	552 (mg/kg sediment dw)
	sediment (marine water)	552 (mg/kg sediment dw)
	Soil	28 (mg/kg soil dw)
	STP	2251 (mg/L)
oral (Hazard for predators)	160 (mg/kg food)	

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Degreaser		
Breathing protection:			
If the recommended technical measures are observed, no individual protection equipment is necessary.			
Hand protection:			
PPE:	Work gloves.		
Characteristics:	«CE» marking, category I.		
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		



-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 8 of 14

Print date: 10/05/2021

Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.
Skin protection:	
PPE:	Protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Work footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN 20347
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour

Colour: Amarillento

Odour: Suave

Odour threshold: N.A./N.A.

pH: 11.4

Melting point: -5 °C

Boiling Point: >100 °C

Flash point: >100 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A.

Lower Explosive Limit: N.A./N.A.

Upper Explosive Limit: N.A./N.A.

Vapour pressure: N.A./N.A.

Vapour density: N.A./N.A.

Relative density: 1.02

Solubility: Alcohols

Liposolubility: N.A./N.A.

Hydrosolubility: Total

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

Oxidizing properties: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 9 of 14

Print date: 10/05/2021

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.

10.3 Possibility of hazardous reactions.

Neutralization can occur on contact with acids.

10.4 Conditions to avoid.

- Avoid contact with acids.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- Corrosive vapors or gases.

SECTION 11: TOXICOLOGICAL INFORMATION.

2-butoxyethanol and its acetate are easily absorbed by the skin and can cause noxious effects to the kidneys.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	Oral	LD50	Rat	5050 mg/kg bw [1]
	Dermal	[1] <i>Gigiena i Sanitariya</i> . For English translation, see HYSAAV. Vol. 43(1), Pg. 8, 1978		
		LD50	Rabbit	12800 mg/kg bw [1]
Inhalation	[1] <i>Raw Material Data Handbook</i> , Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 100, 1974			
sodium hydroxide, caustic soda CAS No: 1310-73-2 EC No: 215-185-5	Oral	LD50	Rabbit	325 mg/kg bw [1]
	Dermal	[1] <i>Naunyn-Schmiedeberg's (1937), Archiv für experimentielle Pathologie und Pharmakologie (Berlin, Germany), 184, 587-604</i>		
		Inhalation		

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 15.714 mg/kg

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 10 of 14

Print date: 10/05/2021

ATE (Oral) = 6.250 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	Fish	LC50	Fish	9640 mg/l (96 h) [1] [1] Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (<i>Pimephales promelas</i>), Vol. 1. Center for Lake Superior Environmental Stud., Univ. of Wisconsin-Superior, Superior, WI :414
	Aquatic invertebrates	LC50	Crustacean	1400 mg/l (48 h) [1] [1] Blackman, R.A.A. 1974. Toxicity of Oil-Sinking Agents. Mar.Pollut.Bull. 5:116-118
	Aquatic plants			
sodium hydroxide, caustic soda	Fish	Minimal Lethal Concentration	Notropis sp.	100 mg/L (120 h) [1] [1] Van Horn et al. (1949), Effects of Kraft Mill Wastes, American Fisheries Society
	Aquatic invertebrates	LC50	Ophryotrocha diadema	33 mg/L (48 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 11 of 14

Print date: 10/05/2021

CAS No: 1310-73-2	EC No: 215-185-5	Aquatic plants	[1] Parker JG (1984), Wat Res, 18, 865-868
-------------------	------------------	----------------	--

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
2-butoxyethanol, ethyleneglycol monobutyl ether, butyl cellosolve CAS No: 111-76-2 EC No: 203-905-0	0,8	-	-	Very low
propan-2-ol, isopropyl alcohol, isopropanol CAS No: 67-63-0 EC No: 200-661-7	0,05	-	-	Very low
CAS No: 141-43-5	EC No: 205-483-3	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 12 of 14

Print date: 10/05/2021

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Not classified as hazardous for transport.

IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 Date of compilation: 31/03/2021

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 13 of 14

Print date: 10/05/2021

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Met. Corr. 1 : Corrosive to metals, Category 1
Skin Corr. 1A : Skin Corrosive, Category 1A
Skin Corr. 1B : Skin Corrosive, Category 1B
Skin Irrit. 2 : Skin irritant, Category 2
STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Changes in the composition of the product (SECTION 3.2).
- Modification in the firefighting measures (SECTION 5.3).
- Modifications in the accidental release measures (SECTION 6.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Change in the hazard classification (SECTION 11.1).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC)

1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
Log Pow: Logarithm of the partition octanol-water.
NOEC: No observed effect concentration.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



MASTERCLEAN CAR BBO

Version 1 **Date of compilation: 31/03/2021**

Version 2 (replaces version 1)

Revision date: 10/05/2021

Page 14 of 14

Print date: 10/05/2021

Regulation (EU) 2015/830.
Regulation (EC) No 1907/2006.
Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.